

Contents

Undecorated Dry Lining / Plasterboard

Undecorated Gypsum Plaster

Undecorated Interior Blockwork or Brickwork

Undecorated Interior Building Boards

Undecorated Interior Rendering

Undecorated Interior Concrete

Previously Painted Surfaces General

Previously Painted Surfaces Gypsum Plaster

Previously Painted Surfaces Affected by Organic Growth

Previously Painted Surfaces Smoke / Nicotine Stained

Previously Painted Surfaces Water Stained

Previously Painted Surfaces Friable and Powdery

Previously Painted Surfaces Distemper

Wallpapered Surfaces

Textured Coatings (Artex Type) Unpainted



earthBorn Emulsion Spec 1: Undecorated Dry Lining / Plasterboard

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Dry Lining / Plasterboard

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Fill any small surface defects with a suitable plaster filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Porous Surfaces - Mist Coat

Apply one mist coat of earthBorn Emulsion (thinned 4 parts paint to 1 part clean water), over all areas to be decorated. Allow a minimum drying time of 4 hours in normal drying conditions.

Surface Filling - after mist coating

Fill any surface imperfections with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust and touch in filled areas with earthBorn Emulsion thinned as for mist coat.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 2: Undecorated Gypsum Plaster

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface

Gypsum Plaster

All surfaces must be clean, suitably dry and free from plaster fines and anything that will interfere with the adhesion of the materials to be applied. Remove any loose material or efflorescence by scraping and dry bristle brushing. Fill any small surface defects with a suitable plaster filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Porous Surfaces - Mist Coat

Fill any surface imperfections with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust and touch in filled areas with earthBorn Emulsion thinned as for mist coat.

Surface Filling - after mist coating

Fill any surface imperfections with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust and touch in filled areas with earthBorn Emulsion thinned as for mist coat.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 3: Undecorated Interior Blockwork or Brickwork

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Blockwork or Brickwork - interior only

All surfaces must be clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove any loose material and mortar splashes by scraping or brushing with a stiff bristle brush.

Porous Surfaces - Mist Coat (*Blockwork Only*)

Apply one mist coat of earthBorn Emulsion (thinned 4 parts paint to 1 part clean water), over all areas to be decorated. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 4: Undecorated Interior Building Boards

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Building Boards - interior only

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. All fixings to be non-ferrous. Fill any small surface defects and fixing holes with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Porous Surfaces - Mist Coat

Apply one mist coat of earthBorn Emulsion (thinned 4 parts paint to 1 part clean water), over all areas to be decorated. Allow a minimum drying time of 4 hours in normal drying conditions.

Surface Filling - after mist coating

Fill any surface imperfections with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust and touch in filled areas with earthBorn Emulsion thinned as for mist coat.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 5: Undecorated Interior Rendering

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Rendering - interior only

All surfaces must be clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove any loose material or efflorescence by scraping and dry bristle brushing. Fill any small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper. Remove all dust.

Porous Surfaces - Mist Coat

Apply one mist coat of earthBorn Emulsion (thinned 4 parts paint to 1 part clean water), over all areas to be decorated. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 6: Undecorated Interior Concrete

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Concrete - interior only

All surfaces must be clean, suitably dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove any loose material or efflorescence by scraping and dry bristle brushing. Remove any snots or fins. Wash with hot water and liquid detergent solution to remove any residual mould oil and any other contaminants, frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry. Fill any small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 7: Previously Painted Surfaces General

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Loose or Flaking Material

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove loose or flaking material by scraping or brushing with a stiff bristle brush to a sound edge. Feather sound edges with a fine grade of abrasive paper. Remove all dust.

Sound Paint

Oil based previous coatings and glossy surfaces should be lightly wet abraded to provide a key. Wash with hot water and liquid detergent solution to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry.

Cracks and Surface Defects

Fill any cracks and small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.



Patch Priming

Patch prime any bare or filled areas with one coat of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 8: Previously Painted Surfaces Gypsum Plaster

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Loose or Flaking Material

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove loose or flaking material by scraping or brushing with a stiff bristle brush to a sound edge. Feather sound edges with a fine grade of abrasive paper. Remove all dust.

Small Repairs to Gypsum Plastering

Remove any small areas of loose gypsum plastering. Remove dust. Dampen edges and areas to be made good. Make good with a suitable plaster repair compound in accordance with manufacturer's instructions. Allow to dry.

Sound Paint

Oil based previous coatings and glossy surfaces should be lightly wet abraded to provide a key. Wash with hot water and liquid detergent solution to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry.



Cracks and Surface Defects

Fill any cracks and small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Patch Priming

Patch prime any bare or filled areas with one coat of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 9: Previously Painted Surfaces Affected by Organic Growth

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Loose or Flaking Material

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove loose or flaking material by scraping or brushing with a stiff bristle brush to a sound edge. Feather sound edges with a fine grade of abrasive paper. Remove all dust.

Organic (Mould/Fungi) Growth

Remove all visible signs of organic growth and treat affected and adjoining areas with a dilute bleach solution (1 part bleach to 15 parts clean water). Rinse thoroughly with clean water to remove all residues. Allow to dry.

Sound Paint

Oil based previous coatings and glossy surfaces should be lightly wet abraded to provide a key. Wash with hot water and liquid detergent solution to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry.



Cracks and Surface Defects

Fill any cracks and small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Patch Priming

Patch prime any bare or filled areas with one coat of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 10: Previously Painted Surfaces Smoke / Nicotine Stained

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Loose or Flaking Material

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove loose or flaking material by scraping or brushing with a stiff bristle brush to a sound edge. Feather sound edges with a fine grade of abrasive paper. Remove all dust.

Smoke / Nicotine Stained Surfaces

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Wash with hot water and liquid detergent to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry. Prime with one coat of earthBorn Volvox Isolating Primer in accordance with the manufacturer's instructions. Allow a minimum drying time of 24 hours in normal drying conditions.

Sound Paint

Oil based previous coatings and glossy surfaces should be lightly wet abraded to provide a key. Wash with hot water and liquid detergent solution to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry.



Cracks and Surface Defects

Fill any cracks and small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Patch Priming

Patch prime any bare or filled areas with one coat of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 11: Previously Painted Surfaces Water Stained

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Loose or Flaking Material

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove loose or flaking material by scraping or brushing with a stiff bristle brush to a sound edge. Feather sound edges with a fine grade of abrasive paper. Remove all dust.

Water Stained Surfaces

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Prime with one coat of earthBorn Volvox Isolating Primer in accordance with the manufacturer's instructions. Allow a minimum drying time of 24 hours in normal drying conditions.

Sound Paint

Oil based previous coatings and glossy surfaces should be lightly wet abraded to provide a key. Wash with hot water and liquid detergent solution to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry.



Cracks and Surface Defects

Fill any cracks and small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust.

Patch Priming

Patch prime any bare or filled areas with one coat of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 12: Previously Painted Surfaces Friable and Powdery

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Loose or Flaking Material

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove loose or flaking material by scraping or brushing with a stiff bristle brush to a sound edge. Feather sound edges with a fine grade of abrasive paper. Remove all dust.

Powdery Surfaces

If surfaces remain powdery and friable even after thorough preparation, treat with a liberal application of earthBorn Wall Glaze in accordance with the manufacturer's instructions. Allow a minimum drying time of 24 hours in normal drying conditions.

Sound Paint

Oil based previous coatings and glossy surfaces should be wet abraded to provide a key. Wash with hot water and liquid detergent solution to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry.



Cracks and Surface Defects

Fill any cracks and small surface defects with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust

Patch Priming

Patch prime any bare or filled areas with one coat of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 13: Previously Painted Surfaces Distemper

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Distemper Coated Surfaces

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove as much as possible of the distemper by scraping, brushing and washing. Allow to dry. Rub down with a fine grade of abrasive paper to remove any remaining distemper residues. Remove all dust.

Porous Surfaces - Mist Coat

Apply one mist coat of earthBorn Emulsion (thinned 4 parts paint to 1 part clean water), over all areas to be decorated. Allow a minimum drying time of 4 hours in normal drying conditions.

Surface Filling - after mist coating

Fill any surface imperfections with a suitable filler in accordance with the manufacturer's instructions. Allow to dry. Rub down with a fine grade of abrasive paper to a smooth level surface. Remove all dust and touch in filled areas with earthBorn Emulsion thinned as for mist coat.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 14: Wallpapered Surfaces

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Wallpapered Surfaces

Ensure that the paper is dry and firmly attached to the surface. Wash with a water and liquid detergent solution to remove any contaminants frequently changing the water. Rinse thoroughly with clean water to remove all residues. Allow to dry.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.



earthBorn Emulsion Spec 15: Textured Coatings (Artex Type) Unpainted

IMPORTANT NOTES / PREAMBLE

- A) Apply all products in accordance with BS 6150:1991 Code of Practice for Painting Buildings and BS 8000: Part 12:1989 Workmanship on Building Sites.
- B) All products should be applied in accordance with the manufacturer's instructions / Product Data Sheets.
- C) If there is any doubt whatsoever with any respect of this specification it must be brought to the attention of the Specifying Authority before pricing.
- D) Every care has been taken to ensure that the information provided in this specification is accurate at the time of issue. earthBorn are however unable to guarantee results since they have no control over the conditions under which their products are applied.
- E) When preparing pre 1960's painted surfaces consideration must be given to taking special precautions as they may contain lead.
- F) Because earthBorn Claypaint is based on natural products occasionally there may be very slight differences in shade between batches, therefore as with all paints, as a precaution avoid starting a new container in the middle of a surface.

Textured Coatings (Artex Type) Old and Unpainted

All surfaces must be clean, dry and free from anything that will interfere with the adhesion of the materials to be applied. Remove any loose material by dry bristle brushing.

Powdery Surfaces

If surfaces remain powdery and friable even after thorough preparation, treat with a liberal application of earthBorn Wall Glaze in accordance with the manufacturer's instructions. Allow a minimum drying time of 24 hours in normal drying conditions.

Porous Surfaces - Mist Coat

Apply one mist coat of earthBorn Emulsion (thinned 4 parts paint to 1 part clean water), over all areas to be decorated. Allow a minimum drying time of 4 hours in normal drying conditions.

Prepared Sound Clean Surfaces

Decorate with two coats of earthBorn Emulsion in accordance with the manufacturer's instructions. Allow a minimum drying time of 12 hours between coats in normal drying conditions.

