

1-610 Technical Information Sheet  
**Volvox Wallpaper Paste**



**1. Use**

Volvox Wallpaper paste is suitable for hanging wallpapers on absorbent surfaces. Note it can also be used in paste-like form as a non-hazardous finger paint.

*The user is recommended to test the product on the intended surface to ensure its suitability*

**2. Product Codes**

100g 1-6101  
500g 1-6102

**3. Instructions for Use**

Disperse Volvox Wallpaper Paste into water while stirring constantly until a lump free paste is obtained. For best results use warm water. Leave to stand for approx 30 minutes and stir thoroughly once more. Apply to wallpaper with a brush or a wallpaper paste machine, ensuring the edges of the wallpaper are fully covered. Attach the wallpaper to the wall pressing evenly and firmly to avoid the formation of air pockets. It is recommended to roller the seams to ensure good adhesion.

**4. Tools**

Brush

**5. Storage**

Keep containers tightly sealed and store in a cool but frost-free and dry place.

**6. Ingredients**

Pure methyl cellulose of various fibre lengths. Guaranteed free from fungicides, preservatives and synthetic resins.

**7. Safety**

Even though non-hazardous, keep out of the reach of children.

**8. Disposal**

Allow unused wallpaper paste to dry and dispose of safely and according to local authority disposal guidelines.



Frodsham Business Centre  
Bridge Lane  
Frodsham  
Cheshire WA6 7FZ  
T: 01928 734171  
F: 01928 731732  
[www.earthbornpaints.co.uk](http://www.earthbornpaints.co.uk)

Data sheets/volvox Wallpaper paste  
Rev: A Jun 05