

Volvox Floor Lacquer



1. Use

Volvox Floor Lacquer is a hard-wearing clear lacquer for heavily used internal surfaces, such as boarded floors, cork and parqueted floors.

2. Product Codes

750ml 2-3502
2.5l 2-3503

3. Coverage

65-75ml per sq m (i.e. 13-15 sq m per litre), depending on the coat thickness required.

4. Colour

Clear

5. Thinner

Volvox Isoparaffin

6. Drying Time

Dry within 24 hours, depending on temperature, relative humidity and surface properties; fully hardened within one week. Please note that applying the lacquer too thickly may prolong the drying time.

7. Instructions for Use

Do not apply in temperatures below 15 deg C. The surface should be clean, grease-free, absorbent and pre-sanded. Stir well before use. For the first coat dilute the lacquer with 20-30% Volvox Isoparaffin. After a drying time of at least 24 hours sand the first coat (grain 240); for floors use a sanding pad (grain 150). Apply two further thin coats with undiluted Volvox Floor Lacquer.

8. Tools

Brush, roller, spraying

9. Storage

Keep containers tightly sealed and store in a cool but frost-free place

10. Ingredients

Linseed oil, soya alkyd, colophony hardened resin, isoparaffin, anti-skinning agent, lead-free dryers.

11. Safety

Product is flammable. Avoid contact with skin; may cause allergic reaction. Keep away from sources of ignition; no smoking during application. Always work in a well-ventilated area. Cloths soaked with the product are self-combustible and must be disposed of in a sealed metal container or spread out to dry.. keep product out of the reach of children.

12. Disposal

Dispose of any product surplus to requirements safely and according to local authority disposal guidelines.

The user is recommended to test the product on the intended surface to ensure its suitability



Frodsham Business Centre
Bridge Lane
Frodsham
Cheshire WA6 7FZ
T: 01928 734171
F: 01928 731732
www.earthbornpaints.co.uk

Data sheets/Volvox Floor Lacquer
Rev. A Jun 05